

QuadCore® B Designwall 2000R-459 Allowable Load / Span Tables

Facer Gauges: 22ga exterior/24ga interior
Support Steel: 14ga

12" Wide								
Panel Thickness	Span Condition	Negative Wind Pressure						
		20 PSF	25 PSF	30 PSF	35 PSF	40 PSF	45 PSF	50 PSF
2.5"	Single	13'-2"	11'-10"	10'-5"	9'-5"	8'-7"	8'-0"	7'-6"
	Double	14'-9"	13'-0"	11'-8"	10'-7"	9'-10"	9'-2"	8'-7"
	Multiple	15'-11"	14'-1"	12'-7"	11'-6"	10'-7"	9'-10"	9'-2"
3"	Single	14'-2"	12'-7"	11'-5"	10'-3"	9'-4"	8'-7"	8'-1"
	Double	14'-11"	13'-1"	11'-8"	10'-8"	9'-10"	9'-1"	8'-6"
	Multiple	16'-2"	14'-1"	12'-7"	11'-5"	10'-7"	9'-10"	9'-2"
4"	Single	15'-6"	13'-9"	12'-5"	11'-4"	10'-6"	9'-7"	8'-8"
	Double	15'-3"	13'-3"	11'-9"	10'-7"	9'-9"	9'-0"	8'-5"
	Multiple	16'-4"	14'-1"	12'-6"	11'-4"	10'-4"	9'-7"	9'-0"

Deflection Limit:	L/180
Fastening Method:	Standard 3-hole concealed clip w/ (2) 1/4" TEK 3 fasteners
Wind Pressure:	Unfactored, ASD, Service Loads
Thermal Differential:	Is EXCLUDED
Minimum Support Steel Properties:	14 ga, grade 50, (FU=65 ksi)
Fastener pull-out values:	Based on published data for 1/4"-14 Triangle Blazer fasteners (1036 lbs/fastener)

24" Wide								
Panel Thickness	Span Condition	Negative Wind Pressure						
		20 PSF	25 PSF	30 PSF	35 PSF	40 PSF	45 PSF	50 PSF
2.5"	Single	12'-1"	10'-10"	9'-7"	8'-8"	7'-11"	7'-2"	6'-6"
	Double	13'-0"	10'-5"	8'-9"	7'-6"	6'-6"	5'-10"	5'-2"
	Multiple	14'-6"	11'-7"	9'-8"	8'-3"	7'-3"	6'-5"	5'-9"
3"	Single	13'-6"	12'-0"	10'-10"	9'-6"	8'-4"	7'-5"	6'-8"
	Double	13'-2"	10'-7"	8'-10"	7'-7"	6'-7"	5'-10"	5'-3"
	Multiple	14'-6"	11'-7"	9'-8"	8'-4"	7'-3"	6'-5"	5'-10"
4"	Single	14'-9"	13'-1"	11'-8"	10'-0"	8'-9"	7'-9"	7'-0"
	Double	13'-4"	10'-9"	9'-0"	7'-8"	6'-9"	5'-11"	5'-4"
	Multiple	14'-7"	11'-8"	9'-9"	8'-4"	7'-4"	6'-6"	5'-10"

Deflection Limit:	L/180
Fastening Method:	Standard 3-hole concealed clip w/ (2) 1/4" TEK 3 fasteners
Wind Pressure:	Unfactored, ASD, Service Loads
Thermal Differential:	Is EXCLUDED
Minimum Support Steel Properties:	14 ga, grade 50, (FU=65 ksi)
Fastener pull-out values:	Based on published data for 1/4"-14 Triangle Blazer fasteners (1036 lbs/fastener)

Notes to tables: Spans shown are for negative uniform loads only. Spans may be governed by other factors including temperature differentials, deflection requirements, structural support gage, or unequal spacing of secondary. Consult Kingspan for specific project applications.

Contact Details

USA

Columbus, OH: 888-332-5862
Modesto, CA: 800-377-5110

info.na@kingspanpanels.com
www.kingspanpanels.us



For the most up to date version of this document,
please scan the QR code or click the link below.

[Latest version here](#)

Care has been taken to ensure that the contents of this publication are accurate, but Kingspan Limited and its subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use or application of products or methods of working are for information only and Kingspan Limited and its subsidiaries accept no liability in respect thereof.
© Kingspan, Granitstone and the Lion Device are Registered Trademarks of the Kingspan Group plc in the US, Canada and other countries. All rights reserved.