





QuadCore® KS Shadowline Interior Data Sheet



QuadCore® KS Shadowline Interior Data Sheet


Insulated Interior Wall and Ceiling Panel System



Product Specification

Insulation core:	QuadCore® Technology
Profile:	Exterior: Shadowline Interior: Shadowline
Embossing:	Exterior: Stucco or non-embossed Interior: Stucco or non-embossed
Gauge:	Exterior: 26, 24, 22 ga Interior: 26, 24, 22 ga
Width:	45 ³ / ₈ "
Thickness:	2", 2 ³ / ₄ ", 3", 4", 5", 6", 8"
Length:	8' - 53'
Orientation:	Vertical
R-value:	≈ 8 per inch per ASTM C518 @ 75°F mean temperature ≈ 9 per inch per ASTM C518 @ 35°F mean temperature

Class-leading
performance
in thermal, fire
resistance and
health &
wellness



A premium engineered wall/ceiling system for interior applications. Specially designed to meet today's high performance standards in a wide variety of environments.

Applications

KS Shadowline Interior panels with QuadCore® are ideal for interior walls and ceilings in cold storage buildings, food and meat processing plants, critical temperature and controlled environment areas as well as in medical or pharmaceutical facilities. The superior engineered joint assures a tight, well designed vapor barrier in enclosures of any size.

Design Features

KS Shadowline Interior panels with QuadCore® utilize a superior joint design with a caulked seal provision that ensures a tight, well designed vapor barrier in enclosures of any size. Panels are produced in the attractive Shadowline stucco embossed or smooth profiles on both the exterior and interior face. Panel coverage is available in standard 45 ³/₈" width.

Customer Options

Choose from several stock colors and USDA approved finishes, or select a finish to match your needs. For interior heavy wash down environments, CLEANsafe 120 Antibacterial PVC as well as stainless steel facings are available.

Member
C E B A
Controlled Environment
Building Association

QuadCore® KS Shadowline Interior Data Sheet

Insulated Interior Wall and Ceiling Panel System

Performance Testing and Approvals

Kingspan insulated panels featuring QuadCore® Technology meet specific building envelope performance criteria and requirements stipulated by US and Canadian building codes.

Test	Procedure	Results			
Fire	FM 4880	Passed: Class 1 Fire Rating of Building Panels or Interior Finish Materials*			
	FM 4882	Passed: Smoke Sensitive Occupancies Interior and Exterior Use*			
	ASTM E84	Flame Spread: 25 or Less /Smoke Developed: 90 or Less			
	CAN/ULC-S102	Flame Spread: 20, Smoke Developed: 45 for panel insulation core			
	CAN/ULC-S138	Passed: Fire growth of foamed plastic insulated building panels in a full scale room configuration			
	NFPA 259	Tested for potential heat of building materials			
Structural	ASTM E72	Vacuum chamber tested. Panel load / span and deflection tables are available			
Thermal Transmission	ASTM C518	Thermal Performance at 35°F mean temperature		Thermal Performance at 75°F mean temperature	
		Thickness	R-Value	Thickness	R-Value
		2	18	2	16
		2.75	24.75	2.75	22
		3	27	3	24
		4	36	4	32
		5	45	5	40
		6	54	6	48
		8	72	8	64
		Bond Strength	ASTM D1623	Panels tested for tensile bond strength of metal to foam	
Sample placed in an autoclave device and pressurized to 2 PSI at 218°F for 2½ hours					
Skin Delamination		No skin delamination with direct pull off pressure up to 1188 psf			
Regional Approvals	City of LA (LADBS)	CCRR 0567; FB 3080			

*Thickness: 2"-8", Width: 45", Min. panel length: 8', Min. gauge: Exterior 26 ga, Interior 26 ga.

For FM compliance, systems must be installed in accordance with FM installation specifications as detailed on ApprovalGuide.com. Please contact technical.NA@kingspanpanels.com for detailed information or refer to ApprovalGuide.com.



Contact Details

USA

DeLand, FL: 877-638-3266
Modesto, CA: 800-377-5110

info.NA@kingspanpanels.com
www.kingspanpanels.us



[Latest version here](#)

Canada

Caledon, ON: 866-442-3594
Langley, BC: 877-937-6562

info.NA@kingspanpanels.com
www.kingspanpanels.ca



[Latest version here](#)

For the most up to date version of this document,
please scan the QR codes above or click the link.

For the product offering in other markets please contact your local sales representative or visit our website.

Care has been taken to ensure that the contents of this publication are accurate, but Kingspan Limited and its subsidiary companies do not accept responsibility for errors or for information that is found to be misleading.

Suggestions for, or description of, the end use or application of products or methods of working are for information only and Kingspan Limited and its subsidiaries accept no liability in respect thereof.

© Kingspan, the Lion Device, and QuadCore are Registered Trademarks of the Kingspan Group plc in the US, Canada and other countries. All rights reserved. © Kingspan Insulated Panels Inc.

